

Refine Search

Search Results -

Terms	Documents
L4 and L9	10

Database:

US Pre-Grant Publication Full-Text Database
 US Patents Full-Text Database
 US OCR Full-Text Database
 EPO Abstracts Database
 JPO Abstracts Database
 Derwent World Patents Index
 IBM Technical Disclosure Bulletins

Search:

L10

Refine Search

Recall Text

Clear

Interrupt

Search History

 DATE: Wednesday, November 23, 2005 [Printable Copy](#) [Create Case](#)

<u>Set</u> <u>Name</u> side by side	<u>Query</u>	<u>Hit</u> <u>Count</u>	<u>Set</u> <u>Name</u> result set
<i>DB=USPT; PLUR=YES; OP=ADJ</i>			
<u>L10</u>	l4 and L9	10	<u>L10</u>
<u>L9</u>	175/122.ccls. or 175/162.ccls. or 175/170.ccls. or 175/195.ccls. or 175/202-205.ccls.	1163	<u>L9</u>
<u>L8</u>	l4 and L7	25	<u>L8</u>
<u>L7</u>	166/377-381.ccls. or 166/77.1.ccls. or 166/77.51-77.53.ccls. or 166/85.1.ccls.	1436	<u>L7</u>
<u>L6</u>	l4 and L5	21	<u>L6</u>
<u>L5</u>	tilt\$3 or incline	205165	<u>L5</u>
<u>L4</u>	(quill or hollow stem or connector) and L3	110	<u>L4</u>
<u>L3</u>	motor and L2	285	<u>L3</u>
<u>L2</u>	(drill pipe or drill string) and L1	437	<u>L2</u>
<u>L1</u>	top drive and connect\$4	1969	<u>L1</u>